



# INDUCTION SERIES

## WET / MARINE

DATE: _____	PROJECT MGR: _____
JOB: _____	
CAT#: _____	
TYPE: _____	



- TASK ①
- PAINTBOOTH ②
- VAPOR DUST ③
- VAPOR ④
- WET DAMP ⑤**
- MARINE ⑥
- EXPLOSION PROOF ⑦
- HID ⑧
- INSPECTION ⑨
- PORTABLE LIGHTING ⑩
- MOUNTING ⑪
- PHOTOMETRY ⑫
- LAMPS BALLASTS ⑬
- INFO ⑭
- CUSTOM ⑮
- ASK THE EXPERT ⑯

### DESCRIPTION

When reliable lighting is required with the ability for instant on and long life the Induction Series is right for the job! This classified product is perfect for those hard to get to places that are abundant in many facilities. This product has an automatic switch off in case of failure, provides warm white light and has exceptional energy efficiency. Designed to operate in ambient temperatures of -40 degree C to +40 degree C and will retrofit to existing LDPI "H Series" applications.

### SPECIFICATIONS

- LISTINGS: Class I Division 2 Groups A,B,C,D  
Class I Zone 2, Groups IIA, IIB, IIC  
Class II Division 1 & 2 Groups E, F, G  
Class III  
UL 595 Marine locations  
Listed for wet locations, NEMA 4X
- ELECTRICAL: Available in 165 watt Induction Lamp
- APPLICATIONS: Suitable for wet locations.  
Off shore Platforms  
Machining, Coal & Grain dust,  
Waste water treatment plants  
Chemical Plants  
Steel Mills
- OPTIONS: UniPak  
Hazcote





# INDUCTION SERIES

WET / MARINE

## PART NUMBERS

TASK	SERIES	LAMP	STARTER	WATT	BALLAST	VOLTAGE	HOUSING	OPTICAL	MOUNT	FINISH	UNIPAK
1 TASK	<b>D:</b>	<b>I:</b>	<b>O:</b>	<b>16:</b>	<b>E:</b>	<b>12:</b>	<b>L:</b>	<b>R5G:</b>		<b>T:</b>	<b>E:</b>
2 PAINTBOOTH	Wet Marine	Induction	STD Fixture	165 Watt Induction Lamp	Electronic Induction Ballast	120V 60 Hz 208/240/277V 50 or 60 Hz 347V 60 Hz CSA	Lg. Tank	Type V Refractor with Wire Guard Type V Refractor		Hazcote	Unipak
3 VAPOR DUST									<b>A2:</b> 3/4" Cone Top Pendant <b>A3:</b> 1" Cone Top Pendant <b>B2:</b> 3/4" Wall Mount <b>B3:</b> 1" Wall Mount <b>C2:</b> 3/4" Ceiling Mount <b>C3:</b> 1" Ceiling Mount <b>F2:</b> 3/4" Flexible Pendant <b>F3:</b> 1" Flexible Pendant <b>HV1:</b> Hazvertor Ring Class I Div. 2 <b>HV2:</b> Hazvertor Ring Class II Div. 1 <b>L4:</b> 1-1/4" Straight Stanchion <b>L5:</b> 1-1/2" Straight Stanchion <b>P2:</b> 3/4" Rigid Pendant <b>P3:</b> 1" Rigid Pendant <b>S4:</b> 1-1/4" 25 Deg. Stanchion <b>S5:</b> 1-1/2" 25 Deg. Stanchion		
4 VAPOR											
5 WET DAMP											
6 MARINE											
7 EXPLOSION PROOF											
8 HID											
9 INSPECTION											
10 PORTABLE LIGHTING											
11 MOUNTING											

## DIMENSIONS (Nominal)

