


The LENM is designed and listed for hazardous, marine, and wet locations. This product is the perfect solution for applications where corrosion resistant lighting fixtures are required.



1 SERIES	2 LENGTH *	3 LAMP/MODULE QTY	4 LED TYPE	5 VOLTAGE	6 OPTIONS
LENM	2: 2 Ft. 4: 4 Ft.  *Nominal	2: (2) LED Tube Lamps <or> (2) LED Modules  3: (3) LED Tube Lamps	LEDT8: LED Tube Lamp LED: LED Modules	V1: 120-277V (50/60Hz)	EM*: Emergency Backup (90 min.) UL924 SS: Stainless steel captive latches  *LED Modules only. Not available with LEDT8.

### CERTIFICATIONS

UL844 / CSA-C22.2 No.137 (Hazardous)  
 CI D2, Grps A, B, C, D  
 CII D2, Grps F, G  
 T-Code: T4  
 UL1598 / CSA-C22.2 No.250 (Wet/Damp)  
 UL1598A (Marine Outside)  
 CRI Ra>80 (Both LED Types)  
 55°C Ambient

### PERFORMANCE

Electrical Performance Table				
LED Type	Length	Wattage (W)	CCT	Lumen
LED Tube Lamp (#LEDT8)	2Ft - 2 Row	18	5,000K	2,200
	2Ft - 3 Row	26		3,100
	4Ft - 2 Row	36		4,440
	4Ft - 3 Row	53		6,190
LED Module (#LED)	2Ft.	32		4,710
	4Ft.	64		9,420

### CONSTRUCTION

Housing - Non-metallic glass reinforced polyester  
 Lens - Frosted DR® Reinforced Acrylic  
 Acetal lens latches  
 Stainless steel mounting brackets  
 1/2" NPT hubs each end (standard)  
 Weights: 2 Ft.= 10lbs. 4 Ft.= 20lbs.

### ELECTRICAL

120-277VAC (50/60Hz)

### FEATURES

5 Year Warranty  
 Field replaceable LED boards and drivers  
 (if applicable)  
 0-10V Dimming

### DIMENSIONS - (NOMINAL)

