

Flood lights for use in hazardous and marine rated locations. This fixture has a die cast housing and cover as well as a fully pivoting steel yoke. Outdoor wet locations. Temperature range: 70W-400W (all) -30°C to 40°C, 1000W HPS -30°C to 40°C, and 1000W MH -30°C to 25°C.



1	2	3	4	5	6	7	8	9	10	11
---	---	---	---	---	---	---	---	---	----	----

1 SERIES	2 LAMP	3 STARTER	4 WATTS
FD: HID Flood	S: High Pressure Sodium H: Metal Halide	0: Standard Fixture (HPS)	10: 100W (HPS only) 15: 150W (HPS only) 17: 175W 20: 200W 25: 250W 40: 400W 00: 1000W
5 BALLAST	6 VOLTAGE	7 HOUSING	8 MOUNT
P: Reactor H: High Reactance C: Constant Wattage Autotransformer	04: 120/208/277/240V (wired 120) 12: 120V 20: 208V 24: 240V 27: 277V 48: 480V (Contact factory for other available voltages)	0: Standard Housing (400W max.) L: Large Housing (1000W)	Y: Yoke (trunnion)
9 BEAM	10 UNIPAK	11 OPTIONS	Notes: All floodlights for use with mogul base lamps. Standard color is gray.
N: Narrow Beam (6x6) (400W max.)	D: Unipak with Diffuse Coated Lamp E: Unipak with Clear Lamp	OF: Single Fuse FF: Double Fuse PW: Pre-wired 3 1/2" Cord BRZ: Bronze Color BLK: Black Color	

LISTINGS

UL 844
CSA 22.2 No. 137.0
UL 1598A Marine Outside
Class I D2 Groups A,B,C,D
NEMA 3R

ELECTRICAL

HPS (High Pressure Sodium): (70 to 1000W)
MH (Metal Halide): (175 to 1000W)
Voltages: 120, 208, 240, 277 or 480

HOUSING

Die cast aluminum housings and covers for excellent strength, light weight and corrosion resistance. Hinged door swings down for easy relamping and maintenance

REFLECTOR

Computer designed for optimal light distribution and efficiency

LENS

Tempered glass lens resists thermal shock
Fully sealed and mechanically retained

MOUNTING

Fully pivoting steel yoke


HID FL

HAZARDOUS LIGHTING

Chemical Processing • Industrial • Oil / Gas • Shipyards / Marine • Water Treatment






DIMENSIONS (Nominal)







MOUNTING

YOKE MOUNT FLOODLIGHTS MOUNTING BRACKETS


	Cat. No.	Description
	9901H	Steel Crossarm Mounting Bracket
	9902H	Pole-Top Mounting Bracket
	9920H	Universal Wall Mounting Bracket

INTEGRAL SLIPFITTER FLOODLIGHTS - MOUNTING BRACKETS

	Cat. No.	Description
	9605	Wall Mount Pipe Bracket (2") with Flange (Prime Coated)
	9605-G	Wall Mount Pipe Bracket (2") with Flange (Galvanized)
	9352	Two Arm Pole-Top Bracket ("Bullhorn")
	9333	Three Arm Pole-Top Bracket ("Bullhorn")

ACCESSORIES

Cat. No.	Description
75-8	Polycarbonate Vandal Shield
75-V	Glare Control Shield



Standard Housing Large Housing