



LE485R

LED BOOTH LIGHTING - REAR ACCESS

Paint and Powder Booths • Blast Booths • Clean Rooms • Prep • Sanding

The LE485R Series is a hinged, **REAR ACCESS**, recessed mount, LED paint booth luminaire. The LE485R is made of a combination of 20 gauge cold rolled steel and .090 aluminum. This LED fixture is available in 4 Ft. lengths with 1, 2, or 3 rows of LEDs; replacing your standard 2, 4, and 6 lamp fluorescent fixture. This fixture can be used with or without optics, has dimming capabilities, and is available with an EM option.



LE485R

V1

| 1 SERIES | 2 SOURCE | 3 VOLTAGE | 4 OPTIC | 5 DIMMING | 6 CCT | 7 WIRE WHIP* |
|--|--|---|------------------------------------|--------------------------------------|--|--|
| LE485R | 43: 43W (1 Row) 62: 62W (1 ROW) 62-2R: 62W (2 Row) 100: 100W (2 Row) 120: 120W (2 Row) 140: 140W (3 Row) 180: 180W (3 Row) | V1: 120-277VAC (50/60Hz) | Blank: None A: Diffused Acrylic | Blank: None D1: 0-10V D2: DALI | 3: 3,500K 4: 4,000K 5: 5,000K | Blank:None WH: Wire Whip (10ft.) *3-wire wire whip standard. Total number of leads dependent on options ordered. |
| 8 OPTIONS | | 9 CORD OPTIONS | | | | |
| SP: Surge Protector (430 joules) EM: Battery/Driver Backup (90min.) | | HC13: Single 3-Pole Male Pole Connector* HC15: Single 5-Pole Male Connector* HC1D: Single 5-Pole Male Connector + Single 2 Pole Dimming* (For use with D1 or D2 dimming) | | | *Models containing HCXX are suitable for Class I, Division 2 Groups A, B, C, D ONLY | |

CERTIFICATIONS

UL844 / CSA-C22.2 No.137 (Hazardous)
CI D2, Grps A,B,C,D
CII D2, Grps F,G
Paint Spray Listed
T Code: CI D2, CII D2=T3C
UL1598 / CSA-C22.2 No.250 (Wet/Damp)
Lumen Maintenance (L70) >54,000 hrs. (reported)
CRI >80
-25°C to 55°C Ambient

CONSTRUCTION

20 gauge white powder coated steel housing
Hinged, rear access panel
Silicone free gaskets
Acrylic diffused lens (optional)
4 Ft. length (nominal)
Clear tempered glass panel
1/2" NPT Hub(s)
Weights: Min: 47lbs. / Max: 71lbs.

ELECTRICAL

120-277VAC
10Ft. 3-wire whip (standard)
6kV Built-in driver surge protection

FEATURES

0-10V Dimming or DALI
Recess mount - Rear access
Withstands up to 71°C bake cycle for 90 minutes with fixture
power interlock off
Emergency/Battery backup option available
Fits the same opening as Slim Light Series
5 year warranty

*These products are Manufactured in the USA with both domestic and imported components;
not all fixture configurations are compliant. Contact LDPI Sales with specific part number
and requirement - Build America, Buy America, TAA or any other federal procurement act
for compliance confirmation. Compliance confirmation can take up to 3 days.

PERFORMANCE

| Source | Voltage (VAC) 50/60Hz | Input Current (A) | Wattage (W) | CCT | Lumen Output* (Lm) | |
|-----------------|-----------------------------|-------------------------|----------------|--------|--------------------|------------------------------|
| | | | | | No Optic | Diffused Acrylic Optic |
| 43 (1 Row) | 120-277 | 0.36-0.16 | 43 | 3,500K | 5410 | 4410 |
| | | | | 4,000K | 5500 | 4500 |
| | | | | 5,000K | 5600 | 4580 |
| 62 (1 Row) | | 0.53-0.23 | 63 | 3,500K | 7660 | 6140 |
| | | | | 4,000K | 7820 | 6270 |
| | | | | 5,000K | 7900 | 6330 |
| 100 (2 Rows) | | 0.83-0.36 | 100 | 3,500K | 12690 | 10050 |
| | | | | 4,000K | 12950 | 10360 |
| | | | | 5,000K | 13080 | 10460 |
| 120 (2 Rows) | | 1.00-0.43 | 120 | 3,500K | 15370 | 12360 |
| | | | | 4,000K | 15690 | 12610 |
| | | | | 5,000K | 15850 | 12740 |
| 140 (3 Rows) | 1.17-0.51 | 140 | 3,500K | 18670 | 14940 | |
| | | | 4,000K | 19060 | 15250 | |
| | | | 5,000K | 19250 | 15400 | |
| 180 (3 Rows) | 1.50-0.65 | 180 | 3,500K | 23000 | 18630 | |
| | | | 4,000K | 23470 | 19020 | |
| | | | 5,000K | 23710 | 19210 | |
| Emergencny Mode | | | 10.4 | 3,500K | 2,500 | 2,020 |
| | | | | 4,000K | 2,550 | 2,060 |
| | | | | 5,000K | 2,590 | 2,090 |



LE485R

LED BOOTH LIGHTING - REAR ACCESS

Paint and Powder Booths • Blast Booths • Clean Rooms • Prep • Sanding




DIMENSIONS



| Source | Dimensions* (in./mm) | |
|--------------|----------------------|-------------|
| | A | B |
| 43 (1 Row) | 10.0" / 254 | 13.0" / 330 |
| 62 (1 Row) | | |
| 62W (2 Row) | 15.0" / 381 | 18.0" / 457 |
| 100 (2 Rows) | | |
| 120 (2 Rows) | | |
| 140 (3 Rows) | 20.0" / 508 | 23.0" / 584 |
| 180 (3 Rows) | | |
| | * Nominal dimensions | |

PANEL CUTOUT DIMENSIONS



| Source | Dimensions* (in./mm) | |
|--------------|----------------------|-------------|
| | C | D |
| 43 (1 Row) | 10.75" / 273 | 7.0" / 178 |
| 62 (1 Row) | | |
| 62W (2 Row) | 15.75" / 400 | 12.0" / 305 |
| 100 (2 Rows) | | |
| 120 (2 Rows) | | |
| 140 (3 Rows) | 20.75" / 527 | 17.0" / 432 |
| 180 (3 Rows) | | |
| | * Actual dimensions | |



1-800-854-0021 www.ldpi-inc.com
LDPI® is a registered trademark of LDPI, Inc. © LDPI, Inc.

Product design and specifications subject to change without notice.
Visit www.ldpi-inc.com for the most current version and photometric data. v.10.13.25