

The LE101 Series is an ordinary location LED fixture that is available in 4 Ft. and 8 Ft. lengths. This fixture is ideal for warehouses, general industrial areas or other locations where task/area lighting is needed.



1 SERIES	2 LUMENS*	3 CCT	4 VOLTAGE	5 SUPPLY
<b>LE101</b>	39: 3900Lm 59: 5900Lm 79: 7900Lm 118: 11800Lm	3: 3500K 4: 4000K 5: 5000K	<b>V1:</b> 120-277V (driver voltage)	<b>C:</b> 6 Ft. blunt end cord <b>CP1:</b> 6 Ft. cord with 120V twist lock plug <b>CP2:</b> 6 Ft. cord with 277V twist lock plug
6 LENGTH*	7 MOUNTING	8 LENS	9 OPTIONS	NOTES
<b>S:</b> 4 Ft. <b>T:</b> 8 Ft.	<b>SM:</b> Surface mount <b>AM:</b> 45° angle mount	<b>AC:</b> Clear acrylic <b>PC:</b> Clear polycarbonate <b>PD:</b> Diffused polycarbonate	<b>EM:</b> Battery/Driver Backup (90 Min.)	Fixtures supplied with a cord are intended for overhead/ceiling mounting with electrical outlet mounted directly overhead. *8 Ft. fixtures are made from (2) 4 Ft. fixtures factory assembled in tandem.

### CERTIFICATIONS

UL 1598  
CSA 22.2 No. 250.0  
UL 8750  
CSA 22.2 No. 250.13  
-20°C to 35°C Ambient Rating

### FEATURES

20 gauge powder coated white housing  
5 Year Warranty  
>50,000 Hours

### PERFORMANCE

4 Ft.: 37, 52, 74, and 111 Watts (3900, 5900, 7900, and 11800 lumens)  
8 Ft.: 74, 104, 147, and 222 Watts (7800, 11800, 15800, and 23600 lumens)  
120-277 Volts

### OPTIONS

Color Temperature:  
3500k  
4000k  
5000k  
Supply Connection:  
Cord with blunt end  
Cord with twist lock plug 120V  
Cord with twist lock plug 277V  
Fixture Length:  
4 Ft.  
8 Ft.  
Mounting:  
Surface mount bracket  
45° angle mount bracket  
Lens:  
Clear acrylic  
Clear polycarbonate  
Diffused polycarbonate  
Emergency Battery Backup



Multi-Point Rear Mount



End Mount Brackets

# LE101

## ORDINARY LOCATION

General Industrial • Task Lighting • Warehouses



### PERFORMANCE

Model	Fixture Width (X)	# Rows	4Ft			8Ft		
			Nominal Lumen Output at 5000K	Wattage	Input Current (A)	Nominal Lumen Output at 5000K	Wattage	Input Current (A)
LE101-39	9-1/8"	1	3900	37	0.31-0.12	7800	74	0.62-0.27
LE101-59	9-1/8"	2	5900	52	0.44-0.19	11800	104	0.88-0.38
LE101-79	9-1/8"	2	7900	74	0.62-0.27	15800	147	1.23-0.53
LE101-118	12-5/8"	3	11800	111	0.93-0.39	23600	222	1.85-0.80

### DIMENSIONS

