


LEVP vapor proof fixtures are designed to replace traditional 100 watt incandescent and 23 watt CFL type fixtures. The LEVP series feature long lasting LED construction and are suitable for wet and damp locations where moisture is present.



This Fixture Series is Discontinued

Please contact LDPI for availability.
Current availability in limited quantities are:

- LEVP-14-U-53-L2-W
- LEVP-14-U-53-L1-P
- LEVP-14-U-53-L2-C



1 SERIES	2 SOURCE	3 VOLTAGE	4 CCT	5 LENS	6 MOUNT
LEVP	14: 14W	U: 120-277VAC (50/60Hz)	53: 5,300K	L1: Clear, Low Profile Polycarbonate L2: Frosted, Low Profile Polycarbonate	C: Ceiling 1/2" NPT (available with L1 & L2 lens only) P: Pendant 1/2" NPT (available with L1 lens only) W: Wall 1/2" NPT

CERTIFICATIONS

UL1598 / CSA-C22.2 No.250 (Wet/Damp)
Lifetime (L70): >50,000 hrs. (reported)
CRI >65
LM-79, LM-80
-34°C to 40°C Ambient
IP66

PERFORMANCE

Source	Voltage (VAC) 50/60Hz	Input Current (A)	Wattage (W)	CCT	Lumens* (Lm)	
					Clear Lens	Frosted Lens
14	120-277	0.12 - 0.05	14	5,300K	1123	890
*Nominal values						

CONSTRUCTION

Cast aluminum housing
Natural aluminum finish (standard)
Low Profile Lens: Polycarbonate
Weight: 3.3 lbs.
1/2" NPT Hubs

ELECTRICAL

120-277VAC

FEATURES

Mounting: Ceiling, Pendant, Wall
Vapor proof
5 Year Warranty



(P) Pendant Mount
(L1) Clear Poly, Low Profile

LEVP

LED WET / DAMP LIGHTING

Food & Beverage Processing • Industrial • Pulp & Paper • Shipyards / Marine • Water Treatment



MOUNTING / DIMENSIONS

Mount Option	Dimensions	Mount Option	Dimensions
(C) Ceiling Mount Low Profile Lens 1/2" NPT Hubs		(W) Wall Mount Low Profile Lens 1/2" NPT Hubs	
(P) Pendent Mount Low Profile Lens 1/2" NPT Hubs			