


LEVP vapor proof fixtures are designed to replace traditional 100 watt incandescent and 23 watt CFL type fixtures. The LEVP series feature long lasting LED construction and are suitable for wet and damp locations where moisture is present.



### AVAILABLE CONFIGURATIONS

LEVP-14-U-53-L2-C  
 LEVP-14-U-53-L1-W  
 LEVP-14-U-53-L2-W  
 LEVP-14-U-53-L1-P

1 SERIES	2 SOURCE	3 VOLTAGE	4 CCT	5 LENS	6 MOUNT
LEVP	14: 14W	U: 120-277VAC (50/60Hz)	53: 5,300K	L1: Clear, Low Profile Polycarbonate L2: Frosted, Low Profile Polycarbonate	C: Ceiling 1/2" NPT (available with L1 & L2 lens only) P: Pendant 1/2" NPT (available with L1 lens only) W: Wall 1/2" NPT

### CERTIFICATIONS

UL1598 / CSA-C22.2 No.250 (Wet/Damp)  
 Lifetime (L70): >50,000 hrs. (reported)  
 CRI >65  
 LM-79, LM-80  
 -34°C to 40°C Ambient  
 IP66

### PERFORMANCE

Source	Voltage (VAC) 50/60Hz	Input Current (A)	Wattage (W)	CCT	Lumens* (Lm)	
					Clear Lens	Frosted Lens
14	120-277	0.12 - 0.05	14	5,300K	1123	890
*Nominal values						

### CONSTRUCTION

Cast aluminum housing  
 Natural aluminum finish (standard)  
 Low Profile Lens: Polycarbonate  
 Weight: 3.3 lbs.  
 1/2" NPT Hubs

### ELECTRICAL

120-277VAC

### FEATURES

Mounting: Ceiling, Pendant, Wall  
 Vapor proof  
 5 Year Warranty



(P) Pendant Mount  
 (L1) Clear Poly, Low Profile

# LEVP

## LED WET / DAMP LIGHTING

Food & Beverage Processing • Industrial • Pulp & Paper • Shipyards / Marine • Water Treatment



### MOUNTING / DIMENSIONS

Mount Option	Dimensions	Mount Option	Dimensions
(C) Ceiling Mount Low Profile Lens 1/2" NPT Hubs		(W) Wall Mount Low Profile Lens 1/2" NPT Hubs	
(P) Pendent Mount Low Profile Lens 1/2" NPT Hubs			