


LEVP vapor proof fixtures are designed to replace traditional 100 watt incandescent and 23 watt CFL type fixtures. The LEVP series feature long lasting LED construction and are suitable for wet and damp locations where moisture is present.



1 SERIES	2 SOURCE	3 VOLTAGE	4 CCT	5 LENS	6 MOUNT
LEVP	14: 14W	U: 120-277VAC (50/60Hz)	53: 5,300K	L1: Clear, Low Profile Polycarbonate L2: Frosted, Low Profile Polycarbonate G1: Clear Glass Globe with Guard G2: Frosted Glass Globe with Guard	C: Ceiling 1/2" NPT (available with L1 & L2 lens only) P: Pendent 1/2" NPT (available with L1 lens only) W: Wall 1/2" NPT

### CERTIFICATIONS

UL1598 / CSA-C22.2 No.250 (Wet/Damp)  
Lifetime (L70): >50,000 hrs. (reported)  
CRI >65  
LM-79, LM-80  
-34°C to 40°C Ambient  
IP66

### PERFORMANCE

Source	Voltage (VAC) 50/60Hz	Input Current (A)	Wattage (W)	CCT	Lumens* (Lm)	
					Clear Lens (Low/Globe)	Frosted Lens (Low/Globe)
L1	120-277	0.12 - 0.05	14	5,300K	1123	890
*Nominal values						

### CONSTRUCTION

Cast aluminum housing  
Natural aluminum finish (standard)  
Low Profile Lens: Polycarbonate  
Globe Lens: Tempered Glass  
Weight: 3.3 lbs.  
1/2" NPT Hubs

### ELECTRICAL

120-277VAC

### FEATURES

Mounting: Ceiling, Pendent, Wall  
Vapor proof  
5 Year Warranty



(C) Ceiling Mount  
(L1) Clear Poly, Low Profile

(W) Wall Mount  
(G2) Frosted Glass Globe w/ Guard

# LEVP

## LED WET / DAMP LIGHTING

Food & Beverage Processing • Industrial • Pulp & Paper • Shipyards / Marine • Water Treatment



### MOUNTING / DIMENSIONS

Mount Option	Dimensions	Mount Option	Dimensions
(C) Ceiling Mount Low Profile Lens 1/2" NPT Hubs		(W) Wall Mount Low Profile Lens 1/2" NPT Hubs	
(P) Pendant Mount Low Profile Lens 1/2" NPT Hubs		(W) Wall Mount Globe Lens with Guard 1/2" NPT Hubs	