LE108

ORDINARY LOCATION LED LIGHTING

General Industrial ● Task ● Warehouses

The LE108 Series is a line of 8ft LED Open Industrial luminaries. It can be used in dry or damp ordinary locations making it ideal for locations such as warehouses, general industrial areas or other locations where task/area lighting is needed. These luminaires can be mounted vertically, horizontally, surface mounted, or hung.



2 Row with Angle Mount Option

LE108		V1		A				
1	2	3	4	5	6	7	8	9

1 SERIES	2 SOURCE	3 VOLTAGE	4 CCT	5 OPTIC	6 DIMMING	7 MOUNTING	8 OPTIONS	9 CORD OPTIONS
LE108	**85:** 85W (1 Row) **110:** 110W (1 Row) **170:** 170W (2 Row) **220:** 220W (2 Row) **260:** 260W (3 Row) **330:** 330W (3 Row)	**V1:** 120-277VAC (50/60Hz)	**3:** 3,500K **4:** 4,000K **5:** 5,000K	**A:** Diffused Acrylic	**Blank:** None **D1:** 0-10V **D2:** DALI	**SM*:** Adjustable Surface Mount **AM:** Angle Mount *SM includes 0°, 30°, 45°, 60° angles	**SP:** Surge Protection **EM:** Battery/Driver Backup (90min.) **WC:** Wireless Control	**WH:** Wire Whip (10ft) **CP:** 6 Ft. Blunt End Cord **CP1:** 6 Ft. Cord w/120V Twist Lock Plug **CP2:** 6 Ft. Cord w/277V Twist Lock Plug **CP3:** 6 Ft. Cord w/120V Straight Blade Plug

CERTIFICATIONS
UL 1598 (Dry or Damp Locations)
CSA 22.2 No. 250.0
45°C Ambient Rating

CONSTRUCTION
Heavy-duty, open industrial fixture
Sturdy 20 gauge steel
8 ft. Length
Durable, white powder coat finish

FEATURES
Programmable Driver
0-10V or DALI
Reduced installation time
CRI >80
Emergency/Battery backup option available

***These products are Manufactured in the USA with both domestic and imported components; not all fixture configurations are compliant. Contact LDPI Sales with specific part number and requirement - Build America, Buy America, TAA or any other federal procurement act for compliance confirmation. Compliance confirmation can take up to 3 days.**

3 Row with Angle Mount Option

Source	Voltage (VAC) 50/60Hz	Input Current (A)	Wattage (W)	CCT	Lumen Output* (Lm) Diffused Acrylic Optic
85 (1 Row)	120-277	0.71-0.31	85	3,500K	10868.41
				4,000K	11262.40
				5,000K	11420
110 (1 Row)		0.92-0.40	110	3,500K	13380.90
				4,000K	13865.97
				5,000K	14060
170 (2 Row)		1.42-0.61	170	3,500K	20956.43
				4,000K	21716.12
				5,000K	22020
220 (2 Row)		1.83-0.79	220	3,500K	25924.31
				4,000K	26864.09
				5,000K	27240
260 (3 Row)		2.17-0.94	260	3,500K	31215.76
				4,000K	32347.36
				5,000K	32800
330 (3 Row)		2.75-1.19	330	3,500K	40161.74
				4,000K	41617.64
				5,000K	42200
Emergency Mode			20	3,500K	2340
				4,000K	2430
				5,000K	2460

LDPI® is a registered trademark of LDPI, Inc. © LDPI, Inc.

Product design and specifications subject to change without notice.
Visit www.ldpi-inc.com for the most current version and photometric data. v.06.08.26

LE108

ORDINARY LOCATION LED LIGHTING

General Industrial ● Task ● Warehouses



STANDARD DIMENSIONS



Rows	Dimensions*(in./mm)	
	A	B
1 & 2	6.5" (165mm)	9" (229mm)
3	9.9" (252mm)	12.5" (317mm)

LE108 ANGLE MOUNT





LE108 ADJUSTABLE SURFACE MOUNT

1 & 2 ROW



3 ROW





LDPI® is a registered trademark of LDPI, Inc. © LDPI, Inc.

Product design and specifications subject to change without notice.
Visit www.ldpi-inc.com for the most current version and photometric data. v.06.08.26